

## **Magnus CS Tubing Anchor Catcher**

The Magnus CS Tubong Anchor catcher is used to anchor downhole equipment from rotating and/or moving up the hole. The anchor is designed to resist up to 12,000 Ft-lbs of torque with a unique cone and slip design while preventing movement up or down hole. It can be set in casing or open hole.

## **Product Specifications:-**

Casing		Recommended	Tool OD	Thursd Commention
Size (inches)	Weight (lbs/ft)	Hole Size (inches)	Tool OD (inches)	Thread Connection Box Up / Pin Down
5-1/2	13.0 - 23.0	4.670 - 5.044	4.375	2-7/8 IF TOOL JOINT / 2-3/8 IF TOOL JOINT
7	17.0 - 23.0	6.366 - 6.538	6.125	3-1/2 IF TOOL JOINT / NO THREA
	26.0 - 35.0	6.004 - 6.276	5.875	3-1/2 IF TOOL JOINT / NO THREA
7-5/8	24.0 - 39.0	6.625 - 7.025	6.375	3-1/2 IF TOOL JOINT / NO THREA
8-5/8	24.0 - 40.0	7.725 - <mark>8</mark> .097	7.500	3-1/2 IF TOOL JOINT / NO THREA
				4-1/2 IF TOOL JOINT / NO THREA



